



5MHz Dual Channel Datalogging

Datalogging function

Stores up to 17,000 data points with 25MS/s dual channel sampling time (50MS/s single channel)

Features:

- · Easy to use menu driven operation
- Internal or External Triggering
- · Auto or Manual setup for horizontal and vertical scaling
- · Single shot mode
- · Window freeze locks waveform in the display
- · Roll Mode for slow repetition waveforms
- · Store and Recall up to 16 waveforms and setups
- Sampling Time: 25MS/s Dual Channel; 50MS/s Single Channel
- 132 x 128 Pixel Super-Twist two level backlit display
- · Data Hold and Low Battery indication
- MultiMeter functions include AC/DC Voltage, Resistance, Continuity, Frequency, RPM, Pulse Width, % Duty Cycle, Max/Min/Avg, Relative, and Compare (Go-NoGo)
- USB Interface and software for transferring waveforms and data



Ordering Information:

3813955MHz Dual Channel Dataloggi**Mg**ultiScope *

cable, Windowscompatible software, and case

MultiScope



Specifications:	Oscilloscope
Bandwidth	5MHz
Max. Sample Rate per Channel	25MS/s (dual channel); 50MS/s (single channel)
Record Length	512 single shot; 256 all other modes
Sample Mode	Single shot, Roll, Normal
Max Vertical Sensitivity	50mV
Max Input Voltage	600V DC or AC rms
Trigger Modes	Auto, Normal, Single
Trigger Source	Channel A, Channel B, External
Trigger Coupling	AC, DC
Timebase	1μS to 5S
Input Impedance	1ΜΩ
Specifications:	Datalogger
Memory	17,000 points
Sampling Rate	0.25S/s to 60S/s
Sampling Mode	Peak, Sampling Time
Clock	Real Time Clock
Specifications:	MultiMeter
DC Voltage	0.1mV to 1000V (0.3% basic accuracy)
AC Voltage (TRMS)	0.m1 to 750V (50-20kHz bandwidth)
Resistance	0.001kΩ to 5MΩ
Continuity	Test voltage 1.7V; threshold 100 digits
Frequency	0.01Hz to 10MHz
RPM	240-60,000
Pulse Width	2μs to 500ms
Duty Cycle	25% to 75%
Dimensions/Weight	7.7 x 3.5 x 1.6" (195 x 90 x 40mm)/1.6lbs (730g)









more infor for Extech 381395

Phone: 01235 838 555

Email: cs@airconcern.co.uk Web. www.airconcern.co.uk