

## Dial Stem Thermometers

✓ Choice of Flat Surface or Penetration Stem Thermometer  
For use in liquids, semi-solids and solids

### Features:

- Flat Surface Stem (Model 392052):  
High temperature range: -58 to 572°F (-50 to 300°C)
- Penetration Stem (Model 392050):  
Temperature range: -58 to 302°F (-50 to 150°C)
- Basic Accuracy of 2°F or 1°C
- 0.1° resolution to 199.9; 1° over 200°
- ON/OFF switch saves battery life
- Auto power off after 1hr of non use
- Dimensions: 5" (130mm) stainless steel probe with 2" (54mm) dial
- Weight: 1oz (29g); 1.3oz (30g) with protective sheath
- Includes 1.5V button battery, and plastic protective sheath with pocket clip for model 392050



Stem thermometer ideal for measuring temperature in HVAC applications such as air ducts, vents, and heaters.

Flat surface stem thermometer ideal for measuring high temperature on motors and other flat surface areas including grills.

### Ordering Information:

392050.....Dial Stem Thermometer  
392052.....Dial Flat Surface Stem Thermometer



**airconcern**

more info for Extech 392052

Phone: 01235 838 555

Email: [cs@airconcern.co.uk](mailto:cs@airconcern.co.uk)

Web: [www.airconcern.co.uk](http://www.airconcern.co.uk)

Air Concern Ltd, Building 173 Curie Avenue Harvell Didcot, Oxfordshire