




Hygro-Thermometer Humidity Alert w/Dew Point

✓ NIST Calibrateable and Programmable Alarms
Warning of High or Low Humidity Conditions

Features:

- Large, easy-to-read triple LCD displays % Relative Humidity, Temperature and Dew Point
- % RH audible and visual alarms, with adjustable set points, alert when humidity exceeds set limit
- Probe clips onto meter or extends on 18" (457mm) cable
- Max/Min with Reset function
- Rear calibration adjustment pot for Humidity and Temperature (available with NIST certification and optional Calibration Standards)
- Complete with built-in stand, wall mount bracket, remote sensor and 2 AAA batteries; Optional calibration salt bottles Model RH300-CAL



Applications:

- In summertime, identifies and warns when conditions for mold growth exist
- In wintertime, identifies and warns when low humidity conditions for static electricity exist
- Remote probe allows for measurements behind walls or in difficult to access locations
- Air temperature and dew point temperature indicate where condensation may occur
- Monitor conditions in laboratories, storage areas and other controlled environment settings
- Ideal solution when traceable ISO calibrations are required by operating standards



| Specifications | |
|----------------|-------------------------------------|
| Humidity | 10 to 99% |
| Temperature | 14 to 140°F (-10 to 60°C) |
| Basic Accuracy | ±4%RH ±1.8°F/1°C |
| Dimensions | 4.3 x 3.9 x 0.78" (109 x 99 x 20mm) |
| Weight | 6oz (169g) |

Ordering Information:

445815Humidity Alert II Hygro-Thermometer with Dew Point
 445815-NIST.....445815 with Calibration Traceable to NIST.
 RH300-CALOptional 33% and 75% RH calibration standards



airconcern

more info for Extech 445815

Phone: 01235 838 555

Email: cs@airconcern.co.uk

Web: www.airconcern.co.uk

Air Concern Ltd, Building 173 Curie Avenue Harvell Didcot, Oxfordshire