


Waterproof ExStik[®] II Dissolved Oxygen Meter/Kit







 Easy to replace screw on membrane cap
For fast replacement and operation. Extension cable and weighted probe guard included with the Kit

Features:

- Convenient kit adds versatility on measuring Dissolved Oxygen in laboratories or out in the field with a 16ft (5m) extension cable and probe weight guard for taking easy measurements in tanks or streams
- Oxygen level displayed as % Saturation from 0 to 200.0% or Concentration from 0 to 20.00ppm (mg/L)
- Adjustable Altitude Compensation (0-20,000ft in 1,000ft increments)
- Adjustable Salinity Compensation from 0 to 50ppt
- Analog bargraph indicates trends
- Memory stores up to 25 data sets with DO and Temperature reading
- Self calibration on power up
- Data Hold, Auto power off, Low battery indicator
- Waterproof to IP57
- Optional 3 ft (1m) or 16ft (5m) extension cable with probe weight.
- DO600 meter includes DO electrode, protective sensor cap, spare membrane cap, electrolyte, four 3V CR-2032 batteries, and 48" (1.2m) neckstrap. See image on right for DO600-K Kit information.



DO600-K —Kit includes DO600 meter, DO603 membrane kit, 16ft (5m) extension cable, weighted probe guard, and hard carrying case — \$125 savings

| | | |
|---|---|---|
|  |  |  |
| Sample testing with extension cable attached to meter | Sample testing with the meter in a laboratory environment | Choice of optional 3ft (1m) or 16ft (5m) extension cable with probe weight |
|  |  |  |
| Extension cable attached to meter | Bonded membrane cap for easy replacement | DO603 Membrane Kit includes 6 screw on membrane caps, 15mL filling solution and polishing paper |

| Specifications | Range | Max Resolution | Basic Accuracy |
|-------------------------|----------------------------|----------------|----------------|
| DO (saturation mode) | 0 to 200.0% | 0.1% | ±2% FS |
| DO (concentration mode) | 0 to 20.00ppm (mg/L) | 0.01ppm (mg/L) | 0.4ppm (mg/L) |
| Temperature | 32 to 122°F (0 to 50°C) | 0.1°F/°C | ±1.8°F (1°C) |
| Dimensions | 1.4x6.9x1.6" (36x176x41mm) | | |
| Weight | 3.8oz (110g) | | |

Ordering Information:

DO600.....ExStik[®] II Dissolved Oxygen Meter
 DO600-K.....ExStik[®] II Dissolved Oxygen Kit
 DO610.....ExStik[®] II DO/pH/Conductivity Kit
 DO603.....Membrane Kit for DO600 and DO605
 DO605.....Spare ExStik[®] II Dissolved Oxygen Electrode module
 EX010.....Extension Cable, 3ft (1 Meter) with probe weight for ExStik
 EX050.....Extension Cable, 16ft (5 Meter) with probe weight for ExStik
 CA895.....Carrying case, Small with Belt Loop
 CA903.....Carrying case for ExStik kit



airconcern

more info for Extech DO600-K

Phone: 01235 838 555

Email: cs@airconcern.co.uk

Web: www.airconcern.co.uk