

Extech 400 Series MultiMeters

Rugged design with built-in IR Thermometer
Extech 400 Series MultiMeters are available with or without the built-in InfraRed thermometer, select auto or manual ranging, True RMS or averaging, and choose the meter you want at a price you can afford.

BUILT IN IR Thermometer
Patented



Common Features:

- Large backlit LCD display with easy-to-read 1" digits
- Type K thermometer built-in for temperature measurements
- Low current capability: measure down to 0.1µA
- Input fuse protection and mis-connection warnings
- Complete with CAT III test leads, multi-position tilt stand and velcro strap for hanging, protective holster with test lead holder, bead wire temperature probe, and 9V battery

Model EX410/EX411

- True RMS (EX411)
- Manual Ranging

Model EX450


- Built-in IR Thermometer
- Autoranging

Model EX420/EX430

- True RMS (EX430)
- Autoranging
- Capacitance
- Frequency

Model EX470

- Built-in IR Thermometer
- True RMS
- Autoranging
- Capacitance
- Frequency
- Relative function



EX400 SERIES



Specifications	EX410	EX411	EX420	EX430	EX450	EX470
Temperature (IR)	—	—	—	—	✓ -58 to 518°F (-50 to 270°C)	✓ -58 to 518°F (-50 to 270°C)
Averaging/True RMS	Averaging	✓ True RMS	Averaging	✓ True RMS	Averaging	✓ True RMS
Basic Accuracy (VDC)	±0.5%	±0.3%	±0.3%	±0.3%	±0.5%	±0.3%
AC Voltage	1mV to 750V	1mV to 750V	0.1mV to 750V	0.1mV to 750V	1mV to 750V	0.1mV to 750V
DC Voltage	0.1mV to 1000V	0.1mV to 1000V	0.1mV to 1000V	0.1mV to 1000V	0.1mV to 1000V	0.1mV to 1000V
AC Current	0.1mA to 20A	0.1mA to 20A	0.1µA to 20A	0.1µA to 20A	0.1µA to 20A	0.1µA to 20A
DC Current	0.1µA to 20A	0.1µA to 20A	0.1µA to 20A	0.1µA to 20A	0.1µA to 20A	0.1µA to 20A
Resistance	0.1Ω to 20MΩ	0.1Ω to 20MΩ	0.1Ω to 40MΩ	0.1Ω to 40MΩ	0.1Ω to 20MΩ	0.1Ω to 40MΩ
Capacitance	—	—	✓ 0.01nF to 100µF	✓ 0.01nF to 100µF	—	✓ 0.01nF to 100µF
Frequency	—	—	✓ 0.001Hz to 10MHz	✓ 0.001Hz to 10MHz	—	✓ 0.001Hz to 10MHz
Temperature (Type K)	-4 to 1382°F (-20 to 750°C)	-4 to 1382°F (-20 to 750°C)	-4 to 1382°F (-20 to 750°C)	-4 to 1382°F (-20 to 750°C)	—	-4 to 1382°F (-20 to 750°C)
Duty Cycle	—	—	✓ 0.1% to 99.9%	✓ 0.1% to 99.9%	—	0.1% to 99.9%
Continuity / Diode	Yes	Yes	Yes	Yes	Yes	Yes
Dimensions	7.4x3.2x2" (187x81x50mm)	7.4x3.2x2" (187x81x50mm)	7.4x3.2x2" (187x81x50mm)	7.4x3.2x2" (187x81x50mm)	7.4x3.2x2" (187x81x50mm)	7.4x3.2x2" (187x81x50mm)
Weight	0.75lbs (342g)	0.75lbs (342g)	0.75lbs (342g)	0.75lbs (342g)	0.75lbs (342g)	0.75lbs (342g)
Warranty	1 year	1 year	1 year	✓ 3 years	✓ 3 years	✓ 3 years

Ordering Information

EX410Manual Ranging MultiMeter
 EX410-NISTEX410 MultiMeter w/ Calibration Traceable to NIST.
 EX411True RMS Manual Ranging MultiMeter
 EX411-NISTEX411 MultiMeter w/ Calibration Traceable to NIST.
 EX420Autoranging MultiMeter
 EX420-NISTEX420 MultiMeter w/ Calibration Traceable to NIST.
 EX430True RMS Autoranging MultiMeter
 EX430-NISTEX430 MultiMeter w/ Calibration Traceable to NIST.
 EX470True RMS Autoranging MultiMeter + IR Thermometer
 EX470-NIST* ..True RMS Autoranging MultiMeter + IR Thermometer w/NIST.

Accessories

CA500Case with shoulder strap and side pockets
 TP873Replacement Bead wire Temperature Probe
 HG500Magnetic Hanging Strap

*NISTL-Limited NIST for Certificate of Traceability to all functions except IR Thermometer



airconcern

more info for Extech EX430

Phone: 01235 838 555

Email: cs@airconcern.co.uk

Web: www.airconcern.co.uk

Air Concern Ltd, Building 173 Curie Avenue Harvell Didcot, Oxfordshire