

4-Wire Earth Ground Resistance Tester Kit

Includes all hardware necessary to measure earth ground
In 4 ranges from 2 to 2000Ω

Features:

- 4-wire, 3-wire, and 2-wire testing
- Large dual line LCD
- Autoranging
- Automatic I (current) spike check
- Automatic P (potential) spike check
- Test Hold function for easy operation
- Automatic Zero adjustment
- AC Earth Voltage
- Data Hold and Auto Power off
- Overrange and low battery indication



Complete with test leads with alligator clips, 4 auxiliary earth bars, hard carrying case, and eight 1.5V AA batteries



Specifications	
Earth Ground Resistance ranges	Ω20Ω/ 200Ω/2000Ω
Basic Accuracy	±(2%rdg+3d)
Resolution	0.01Ω/ 0.1Ω/1Ω/0.01kΩ
Test Current / Frequency	<2mA / 820Hz
AC Earth Voltage / Frequency	0 to 300VAC / 40 to 500Hz
Accuracy	±(2%rdg+3d)
Power supply	Eight 1.5V 'AA' Batteries
Dimensions	9.8 x 7.8 x 4.3" (250 x 190 x 110mm)
Weight	3.15lbs (1430g) (batteries included)

Ordering Information:

GRT3004-Wire Earth Ground Resistance Tester Kit
 GRT300-NISTL*..GRT300 with Certificate Traceable to NIST
 382153.....Replacement Earth Bars (2pk)
 382154.....Replacement Set of Leads
 *Limited NIST for Certificate of Traceability to 4-wire mode only



airconcern

more info for Extech GRT300

Phone: 01235 838 555

Email: cs@airconcern.co.uk

Web: www.airconcern.co.uk

Air Concern Ltd, Building 173 Curie Avenue Harvell Didcot, Oxfordshire