


Light Meter/Datalogger

- Records data on an SD card in Excel * format
For easy transfer to a PC for analysis

Features:

- Wide range to 10,000Fc or 100kLux
- Cosine and color-corrected measurements
- Utilizes precision silicon photo diode and spectral response filter
- Datalogger date/time stamps and stores readings on an SD card in Excel * format for easy transfer to a PC
- Offset adjustment used for zero function to make relative measurements
- Adjustable data sampling rate: 1 to 3600 seconds
- Stores 99 readings manually and 20M readings via 2G SD card
- Type K/J Thermocouple input for high temperature measurements
- Large backlit LCD display
- Record/Recall MIN, MAX readings
- Data Hold plus Auto power off with disable function
- Built-in PC interface
- Complete with 6 x AA batteries, SD card, hard carrying case and light sensor with protective cover



Specifications	Range	Resolution	Basic Accuracy
Fc Range	200, 2000, 10kFc	0.1Fc	±4%rdg
Lux Range	2000, 20k, 100kLux	1Lux	±4%rdg
Type K Temperature	-148 to 2372°F (-100 to 1300°C)	0.1°	±(0.4% + 1.8°F/1°C)
Type J Temperature	-148 to 2192°F (-100 to 1200°C)	0.1°	±(0.4% + 1.8°F/1°C)
Memory	20M data records using 2G SD card		
Dimensions	7.2 x 2.9 x 1.9" (182 x 73 x 47.5mm)		
Weight	16.2oz (475g)		

Ordering Information:

- SDL400.....Light Meter/Datalogger
- SDL400-NISTSDL400 w/Certificate of Calibration Traceable to NIST standards
- 872502 Type J Bead Wire Probe (-328 to 392°F/-200 to 200°C)
- TP870 Type K Bead Wire Probe (-40 to 482°F/-40 to 250°C)
- TP200 Type K Clamp Probe (-4 to 200°F/-20 to 93°F)
- TP400 Type K Clamp Probe (-4 to 450°F/-20 to 232°C)
- 153117 117V AC Adaptor
- UA100-240..... 100-240V AC Adaptor with 4 plugs (US, EU, UK, AU)



airconcern

more info for Extech SDL400

Phone: 01235 838 555

Email: cs@airconcern.co.uk

Web: www.airconcern.co.uk

Air Concern Ltd, Building 173 Curie Avenue Harvell Didcot, Oxfordshire