


pH/ORP Electrodes

-  Choice of Standard or Specialized electrodes
BNC connector for use with virtually any pH meter

Features:

- All pH electrodes are Ag/AgCl gel filled (fast response: 95% in 5sec)
- Include 39" (1m) cable with BNC connection and storage solution bottle or cap. 6 month warranty

General purpose pH/Ref electrodes

60120B and 601500:

- Rugged, polycarbonate construction features glass pH sensing bulb surrounded by protective teeth. pH range (0 to 14pH), operating temperature (0 to 80°C). Choice of Mini or Standard size.

Flat surface electrode (Easy to clean) 601100:

- PVC bodied electrode, ideal for pH of solid products with minimal moisture like cheese, soils or electrophoretic/agar gels. pH range (0 to 14pH), operating temperature (5 to 80°C).

Redox ORP/Ref electrode 67500B:

- Platinum sensing surface, polycarbonate body and sealed reference



60120B - Mini size



601500 - Standard size



601100 - Flat Surface



67500B - Redox ORP



pH electrodes (except model 60120B) come with storage bottle with solution to prolong electrode life.

Ordering Information:

- 60120B.....Mini Electrode (10 x 120mm)
601500.....Standard pH Electrode (12 x 160mm)
601100.....Flat Surface Electrode (15 x 106mm)
67500B.....Redox ORP/Ref Electrode (13 x 154mm)



airconcern

more info for Extech 601500

Phone: 01235 838 555

Email: cs@airconcern.co.uk

Web: www.airconcern.co.uk

Air Concern Ltd, Building 173 Curie Avenue Harvell Didcot, Oxfordshire